

WIND

Ultrasonic Anemometer 1D

Part number: 4.3865.0x.xxx

Different measuring values are available, among others:

- Flow vector
- Scalar flow velocity
- Acoustic-virtual temperature
- Standard deviation of the wind velocity
- Standard deviation of the scalar air flow
- Standard deviation of the acoustic-virtual temperature
- Flow velocity of the gust

The instrument is especially suited for the use

- In the traffic engineering
- Indoor flow measurement
- In tunnels
- In tubes

The measurement principle allows, compared to the classic anemometers, an inertia-free measurement of running variable dimensions with highest precision and accuracy. It is especially suited for the measurement of gust- and peak values. The measuring values can be output digitally and/or in analogue form. The serial or analogue output of the data is carried out alternatively as instantaneous value or as gliding mean value with selectable time frame.

If necessary, the sensor arms are automatically heated with critical ambient temperatures.



Specification

Part number: 4.3865.0x.xxx

| Wind speed | |
|---------------------|--|
| Measuring range | 0 ... 75 m/s |
| Resolution | 0.1 m/s |
| Accuracy | ±0.1 m/s rms (< 5 m/s) ±2 % rms (> 5 m/s) |
| Wind direction | |
| Measuring range | 1 or 181 ° |
| Virtual temp. | |
| Measuring range | -50 ... +80 °C |
| Resolution | 0.1 K |
| Accuracy | ±0.5 K |
| Data output digital | |
| Interface | RS485 / RS422 |
| Baudrate | 1200 ... 921600 Baud |
| Data values | instant. values, average values |

| | |
|---------------------------|--|
| Output range | 1 per 10 msec up to 1 per 60 sec |
| Status signals | heating, distance error |
| Data output analog | |
| Wind speed | 0 ... 20 mA 4 ... 20 mA 0 ... 10 V 2 ... 10 V |
| Stromausgang | max. 400 |
| Voltage output | min. 4000 |
| Resolution | 16 bit |
| Operating voltage | |
| Electronic | 8 ... 42 V DC or 12 ... 28 V AC / 2.5 W |
| Heating | 24 V AC/DC, typ 40 W |
| General | |
| Bus operation | up to 98 sensors |
| Electr. connection | 5 m cable |
| Mounting | plate with holes |
| Housing | stainless stell (V4A) AiSi316Ti |
| Protection | IP 67 |
| Dimension | 424 mm x 287 mm |
| Weight | 2.5 kg |

Versions

As per 4.3865.0x.xxx, but:


Product number 4.3865.00.340

| | |
|----------------------------|--------------------------|
| Data output digital | |
| Baudrate | 9600 Baud |
| Duplex mode | Full duplex |
| Data telegram | VDT-Telegram (Telegram2) |
| Output range | 10 per 1 sec |

Product number 4.3865.01.310

| | |
|----------------------------|----------------------------|
| Data output digital | |
| Baudrate | 9600 Baud |
| Duplex mode | Half duplex |
| Data telegram | no independent data output |
| Data output analog | |
| Type | 3 x 4 ... 20 mA |

Accessories

| Product | Product name | Brief description | |
|---|---|---|--------------------------|
|  | Ultrasonic Bird deflector 4.3800.90.000 | The Ultrasonic Bird Deflector protects the ultrasonic anemometer against measurement faults, which might be caused by different species of birds. | |
| | | Data output digital | |
| | | Switching output | max. 24 V AC/DC |
| | | Interface | |
| | | Type | RS485 |
| | | Data format | 8N1 |
| | | Baud rate | 2400 ... 115200 Baud |
| | | General | |
| | | Power supply | 12 ... 24V DC 24 V AC |
| | | Electr. connection | cable gland |
| | | Housing | Polycarbonate |
| | | Protection | IP 65 |
| | | Weight | 0.2 kg |

