

Max. Temp	Single/Duplex	Accuracy	Head	Fittings
200C	<ul style="list-style-type: none"> • single • duplex 	<ul style="list-style-type: none"> • class B • 1/3 DIN • class A 	<ul style="list-style-type: none"> • none • Aluminum head • White polypropolene head 	<ul style="list-style-type: none"> • 1/2"NPT single sided • 1/2" x1/2" NPT double sided • 1/4" NPT adjustable compression • 1/2" X 1/2" NPT spring loaded
400C	<ul style="list-style-type: none"> • single • duplex 	<ul style="list-style-type: none"> • class B • class A 	<ul style="list-style-type: none"> • none • Aluminum head • White polypropolene head 	<ul style="list-style-type: none"> • 1/2"NPT single sided • 1/2" x1/2" NPT double sided • 1/4" NPT adjustable compression • 1/2" X 1/2" NPT spring loaded
600C	<ul style="list-style-type: none"> • single • duplex 	<ul style="list-style-type: none"> • class A 	<ul style="list-style-type: none"> • none • Aluminum head • White polypropolene head 	<ul style="list-style-type: none"> • 1/2"NPT single sided • 1/2" x1/2" NPT double sided • 1/4" NPT adjustable compression • 1/2" X 1/2" NPT spring loaded
800C	<ul style="list-style-type: none"> • single 	<ul style="list-style-type: none"> • class A 	<ul style="list-style-type: none"> • none • Aluminum head • White polypropolene head 	<ul style="list-style-type: none"> • 1/2"NPT single sided • 1/2" x1/2" NPT double sided • 1/4" NPT adjustable compression • 1/2" X 1/2" NPT spring loaded